

KC14

DETALE CPH is a line of exclusive decorative products to take care of the small details. Paints and finishes are inspired by our Nordic design heritage and the changeability of nature.

Product properties

Coloured decorative plaster for walls and ceilings. Finish using DETALE Topcoat. Produces a textured faux surface with depth. Recommended for premises with medium functional requirements, that are exposed to dirt and moderate wear and tear.



- Faux finish with depth
- Matte and velvety smooth finish
- Dirt resistance corresponding to a matt painted surface

Labelling



Product use

Living rooms, entrances, offices, business premises, clinics, shops, hotels and restaurants. Concrete, light concrete, plaster, brick, gypsum board and previously painted surfaces.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning, sanding and dusting.
Remove dirt, grime, grease and flaking material by cleaning thoroughly.
Sand flat hard, slippery surfaces.
Cracks, unevenness and holes must be filled.
Apply twice before application of DETALE Topcoat.

Application

Spread with a wide spatula in an even, covering layer.
Work the filler and smooth it out as you go.
Decide your choice of tools based on the size of the surface.
Cold/heat can affect the viscosity of the material.
Avoid condensation formation.
Cold and increased humidity extends drying time, full curing and recoating interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Risk of shrinkage where the filler paste is not completely cured before additional treatment.
Always test for control and acceptance of adhesion and result.

Expected result

Even, faux surface finish.
The surface does not become rock hard, and it is therefore susceptible to bumps and scratches.
Withstands cleaning with a mild cleaning agent without abrasive material, water and drying with a moist cloth.
Avoid placing loads on the surface before the treatment is fully cured.

Useful Information

The look reflects how the filler was applied.
Be sure to apply filler in soft arches and avoid applying in the same direction.
Bubbles can appear and help emphasise the natural look.

Environmental information

Remove as much plaster as possible before cleaning with water. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage

Cool, frost free and tightly closed

Technical Data

Product Type	Plaster & Sealant
Density (kgs/l)	1.08
Solids Weight %	59
Solids Vol. %	55
Nominal spreading rate (m²/ltr.)	2
Long spreading rate (m²/l.)	1
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Recoatable at 20° C, 60 % RH (Hours)	16
Fully cured at 20° C, 60 % RH (Days)	28
Layer thickness (nominal mm)	4
Cleaning of Tools etc.	Water

Current TDS Version

June 2025

Replaces TDS Version

December 2024