

Wallpaper Remover

Properties

Concentrated, effective wetting agent for removing wallpaper or limepaint. The wallpaper glue is softened so that the wallpaper can be torn off in large pieces.

Use

Suitable for removing wallpaper or distemper.

The wallpaper glue is softened, so that the wallpaper can be torn off in big pieces. Untreated as well as painted wallpaper can be sanded with coarse sanding paper or a notching device, so that the wallpaper softener can penetrate into the glue.

Application

The wallpaper softener is applied in an even and ample layer by paste brush. After 5-20 minutes the wallpaper can be torn off, scraped down by wallpaper scraper or putty knife. Repeated treatment can be necessary. Any spillage on floors or painted surfaces must be wiped off immediately.

Please note!

Must not be added the water of the steam wallpaper remover nor be used as pre-treatment in connection with a steam wallpaper remover.

Environmental information

Remove the cap before recycling

Storage: Cool, frost free and tightly closed



Technical Data

Product Type	Cleaning
Density (kgs/l)	1.02
pH	7
Mixture proportion	Ordinary wallpaper: 0.5 dl to 8-10 liters of water. Heavy wallpaper: 1 dl to 8-10 liters of water.
Contains	AQUA TRIDECETH-10 ISODECETH-5 PROPYLENE GLYCOL BUTOXYDIGLYCOL
Dosing	1:20
Dilution	Water
Cleaning of Tools etc.	Water

Current TDS Version

July 2022

Replaces TDS Version

December 2021