

# Wall Fixer

## Product properties

Quick-drying, white-pigmented primer that produces a matt surface. Especially suitable for priming of paper wallpaper, where you do not want to remove existing firm wallpaper. Reduces blistering when setting up new wallpaper on existing wallpapered surfaces.

- Priming paint
- Pigmented
- Matt



## Labelling



## Product use

Used for priming previously wallpapered surfaces before treatment with wallcovering. Previously wallpapered surfaces must be fixed to substrate and have a good adhesion to the substrate.

## Substrate

Must be clean, dry, firm and suitable for surface treatment.

## Treatment

Remove loose material and paint by cleaning and sanding.

Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.

Water-soluble discolouration, nicotine and soot can be cleaned with Fluren 49.

Sand surface if needed.

Loose wallpaper that forms blisters is removed and primer is repeated.

Cracks, unevenness and holes must be filled.

## Application

Brush, roller or spray.

Decide your choice of tool/utensil depending on the finish.

Apply wet on wet and finish by brushing/rolling in the same direction.

Cold/heat can affect the viscosity of the material.

Material temperature for spray painting, min. 12°C.

Condensation during drying/curing must not occur.

Cold and increased humidity extends drying time, full curing and recoat interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always perform a test treatment for a check and acceptance of adhesion and result.

## Expected result

Matt, covered surface.  
Finished treatment with wallcovering.

## Environmental information

Minimize your paint waste by pre-estimating how much paint you need.  
Remove as much paint as possible from tools before cleaning.  
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.  
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.  
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

## Storage

Cool, frost-free, and tightly closed

## Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.  
Avoid inhalation of spray mist and grinding dust.  
Wear suitable protective equipment, see safety data sheet for further information.

## Technical Data

Product Type	Priming paint
Gloss	Matte
Density (kgs/l)	1.13
Solids Weight %	38
Solids Vol. %	30
Nominal spreading rate (m²/ltr.)	6
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Water
Cleaning of Tools etc.	Water

## Current TDS Version

December 2024

## Replaces TDS Version

September 2024