

Structure 1 ½

Properties

Type: Acrylic dispersion structure paint. Flügger Structure 1 ½ is a coarse-grained structure paint with good application properties. Structure paint provides a coarse-grained and rustic white surface, which is elastic and washable. Decorative effect - from fine to very coarse structure - depending on degree of dilution or use of tools.



Use

Suitable for treatment and structuration of walls and ceilings. Covers minor cracks in the ground.

The surface must be clean, dry, solid, and suitable for painting. Cleaning before treatment should be made with Fluren 37, Basic Cleaner.

Slightly chalking or absorbent surfaces should be primed with Flügger Sealer.

Finest structure is obtained with a wide brush or short-piled roller. Coarse to very coarse structure is obtained with long-piled roller or coarse-pored foam roller. Effect structure can be achieved with putty knife, dabbing with paint brushes, brushes or the like.

Can be applied in a layer up to 5 mm.

Should be painted with Flutex 10/20 or Dekso 5/25.

Storage: Cool, frost-free and tightly closed

Technical Data

Product Type	Acrylic paint
Gloss	Matte
Density (kgs/l)	1.72
Solids Weight %	73
Solids Vol. %	53
Nominal spreading rate (m ² /ltr.)	1
Min. working temp. during application and drying/curing	Min. +5°C
Drying time at 20° C, 60 % RH (Hours)	2
Recoatable at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Water, normally used undiluted
Cleaning of Tools etc.	Water

Current TDS Version

July 2022

Replaces TDS Version

September 2010