

Linseed oil Putty

Product properties

Flügger Linseed Oil Putty is a stabilised oil-based putty which, in addition to traditional alkyd and linseed oil paints, can be overpainted with water-based paints and wood protection such as Flügger Wood Tex Window and Flügger Wood Tex 04.

- Good working consistency
- Becomes hard over time
- Can be painted over with water-based paints and wood protection



Product use

For indoor and outdoor use to fill holes and cracks in woodwork. Particularly suitable for filling gaps when fitting glass and repairing old windows. Does not shrink.

Substrate

Must be clean, dry, solid and suitable for surface treatment. The substrate must be primed or have been previously treated.

Treatment

Clean, sand, and remove loose material and paint.
Remove dirt, grime, grease and chalking materials by cleaning.
New absorbent, porous or discoloured substrates are primed.
Apply the putty and smooth out.
Can be painted over as soon as the film has reached a sufficient thickness.
Should be painted over 1–2 mm inwards from the edge of the glass.

Application

Apply and smooth out using a putty knife or a spatula.
Decide your choice of tools based on the size of the surface.
Apply a sufficient amount and then work and smooth out the filler paste.
Cold/ heat can affect the viscosity of the material.
Condensation must not occur.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Even surface for additional treatment.

Environmental information

Remove as much sealant as possible from your tools before cleaning.
Do not pour leftover sealant down the drain; take it to your local recycling centre.
Minimise your paint waste by calculating in advance how much you will need.
Store any leftover sealant correctly so that it can be reused, thereby minimising the environmental impact.

Storage

Cool, frost-free, and tightly closed

Supplementary Info

Shelf life: 24 months in unopened container.

Technical Data

Product Type	Oilbased products
Density (kgs/l)	2
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max. humidity 80 % RH.
Dry to touch at 20° C, 60 % RH (Hours)	24
Cleaning of Tools etc.	White spirit
Country of Origin	Denmark

Current TDS Version

September 2026

Replaces TDS Version

April 2024