

# Facade Clean

## Product properties

Highly effective alkaline cleaning agent for cleaning painted wood and masonry. Effectively cleans all types of dirt.

- Effectively cleans all types of soiling
- Can be sprayed on
- Excellent for wood, brick and metal



## Product use

Used for cleaning very dirty painted wood, masonry and sheet metal before painting.

## Substrate

Surfaces must be clean, dry, solid and suitable for treatment.

## Treatment

Remove loose material and paint by cleaning and sanding.  
Effectively removes all types of soiling.

## Application

Dose according to instructions.

Apply with a paintbrush, brush or low-pressure spray.

Avoid cleaning warm surfaces which have been exposed to sunshine as this can lead to an uneven gloss on painted surfaces.

Pre-water highly absorbent surfaces.

Allow the solution to work for 5-20 min. without drying out.

The surface can then be scrubbed with a brush to effectively dissolve the dirt.

Afterwards, rinse thoroughly with clean water until all the cleaning agent has been removed.

## Expected result

Clean surface ready for paint treatment, if desired.

## Please note!

Avoid applying to surfaces that have been heated by the sun.

## Environmental information

Remove the cap before sorting the packaging for recycling.

## Storage

Cool, frost-free and tightly closed

## Technical Data

---

Product Type	Cleaning
pH	9
Mixing ratio	Periodic cleaning: 1 litre per 15 litres of water. Washing before painting: 1 litre per 5 litres of water.
Dosing	1:5
Nominal spreading rate (m <sup>2</sup> /ltr.)	6
Min. working temp. during application and drying/curing	Min. +5°C
Dilution	Water
Cleaning of Tools etc.	Water
Country of Origin	Sweden

---

## Current TDS Version

March 2025

## Replaces TDS Version

May 2024