Wall Paint 5

Product properties

Eco-labelled acrylic ceiling and wall paint with extra good coverage. Easy and quick application, gives a nice matte finish. Recommended for premises with normal functional requirements, that are exposed to moderate dirt and wear and tear.



- **Wall and ceiling paint**
- **Easy and quick application**
- **Excellent hiding power**

Labelling

Product use

Living rooms, bedrooms and other living spaces.
Felt- and glasstissue, wallpaper, concrete, light concrete and well-bonded sandplaster.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.
Remove dirt, grime, grease and chalking materials with Fluren 37.
Discolouration from nicotine or soot must be cleaned with Fluren 49 and treated with Stop Primer.
Cracks, unevenness and holes must be spackled.
Absorbent and porous substrates must be primed with Flügger Sealer.
Apply 1-2 times. Some colours require an extra treatment.

Application

Brush or roller.
Decide your choice of tool/utensil depending on the finish.
Apply wet on wet and finish by brushing/rolling in the same direction.
Always use the same batch number on contiguous/unbroken surfaces.
Condensation during drying/curing must not occur.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result
Matt surface.
Withstands after curing cleaning with mild detergents and a damp cloth.
Strong especially dark shades are more delicate than light by wear and touch.
Chalking from strong shades due to excess pigment may occur.
Does not block strike-through from knots or water-soluble colourants, water stains and nicotine.
Exercise care in loading the surface until the paint is fully cured.
Risk of crackling when applied directly to surfaces treated with filler.

Environmental information
Minimize your paint waste by pre-estimating how much paint you need.
Remove as much paint as possible from tools before cleaning.
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage
Cool, frost free and tightly closed

Protection equipment
Protect skin and eyes from splashes with suitable clothing, gloves and glasses.
Avoid inhalation of spray mist and grinding dust.
Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Gloss	Matte;5
Density (kgs/l)	1.46
Solids Weight %	57
Solids Vol. %	37
Nominal spreading rate (m²/ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Dry to touch at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	2
Fully cured at 20° C, 60 % RH (Days)	28
Emission acc. to ISO 16000-9:2011 (< µg/m²h after 28 days)	10
Washability acc. to EN-13300/ISO-11998	Class 2
Dilution	Water, is usually not diluted
Cleaning of Tools etc.	Water and soap

Current TDS Version

December 2025

Replaces TDS Version

December 2024