Ding-dong

Product properties
Colored vinyl chips for mixing in ding-dong Varnish.

- **Colored vinyl chips**
- **Stir into ding-Dong varnish**
- **Robust surface**



Product use
Used together with ding-dong varnish.
Cannot be used in ordinary varnish or paint.

Substrate
Must be clean, dry, solid and suitable for surface treatment.

Treatment
Add 100 g chips to 2½ liters of varnish and 4 x 100 g chips to 10 liters of varnish.
Vinyl chips are best stirred in with a mixer and low revolutions for approx. 5 minutes.
The ready-mixed ding-dong Varnish must be used immediately after mixing.

Application
Brush or roller.
Condensation during drying/curing must not occur.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result
Semi-matt, colourless and durable surface with distinct gloss.
Withstands cleaning with mild detergents without abrasives, water and wiping with a damp cloth.
Exercise care in loading the surface until the paint is fully cured.

Please note!
It must be expected that, possibly remains can cause discoloration as chip soften after some time.

Environmental information
Remove as much paint as possible from tools before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage
Cool, frost free and tightly closed

Technical Data

Cleaning of Tools etc.	Water and soap

Current TDS Version

October 2025

Replaces TDS Version

November 2023