Wall Primer



Product properties

White-pigmented interior priming paint for priming of mineral substrates before painting with topcoat. Provides a uniform substrate before further treatment. The white colour helps revealing and detecting defects in the substrate before applying the finish paint. Recommended for moderately absorbent substrates.

- **Improves topcoat performance**
- **Evens out and uniforms the absorbency of the substrate**
- **The white colour helps detecting defects in the substrate**

Product use

Priming of plaster, concrete, cardboard-coated gypsum board and filled surfaces before painting with ceiling and wall paint.
Recommended for moderately absorbent substrates.
Priming of untreated mineral surfaces while detecting substrate irregularities.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.
Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.
Water-soluble discolouration, nicotine and soot can be cleaned with Fluren 49 or a similar product.
Sand surface to matt finish as required.
Cracks, unevenness and holes must be filled.
For very absorbent substrates, it is recommended to use Flügger Sealer non-drip instead of Flügger Wall Primer White. These products cannot be used at the same time.
Do not apply Flügger Wall Primer White to previously painted and non-absorbent surfaces.

Application

Brush, roller or spray.
Stir before use.
Decide your choice of tool/utensil depending on the finish.
Apply wet on wet and finish by brushing/rolling in the same direction.
Cold/heat can affect the viscosity of the material.
Material temperature for spray painting, min. 12ºC.
Condensation during drying/curing must not occur.
Cold and increased humidity extends drying time, full curing and recoat interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Matt, white surface.
Finish treatment with paint in desired gloss and colour.

Useful Information

If the entire contents of the container are not used during a single application, it is recommended to work from a separate bucket or paint tray rather than directly from the original container, as repeated opening and exposure to air may affect the paint's properties and shelf life.
Therefore, only pour the amount of paint required into a separate bucket or paint tray.
Use plastic bags or inserts to keep the paint tray or bucket clean.
Keep the paint covered during breaks to prevent drying out.
Do not pour leftover paint back into the original container.
To minimize waste, it is recommended to pour only the amount of paint required as work progresses.
For storage, the paint may advantageously be transferred to a smaller, tightly sealed container suitable for the remaining quantity.

Please note!

On a chalking substrate and on a gypsum-based filler, Flügger Sealer Non-drop is recommended as a primer.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.
Remove as much paint as possible from tools before cleaning.
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.
Avoid inhalation of spray mist and grinding dust.
Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Product Type	Priming paint
Density (kgs/l)	1.28
Solids Weight %	39
Solids Vol. %	26
Nominal spreading rate (m²/ltr.)	6
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Dry to touch at 20° C, 60 % RH (Hours)	1
Recoat interval at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	7
Dilution	Do not dilute
VOC Text	VOC limit value (Cat. A/h): 30 g/l (2010) Product VOC: max 2,5 g/l
Cleaning of Tools etc.	Water and soap
Country of Origin	Poland

Current TDS Version

October 2026

Replaces TDS Version

July 2025