Wall Paint Acryl 3

Product properties
Semi-matt very robust wall paint with good adhesion. Very easy to clean and suitable for walls with a certain degree of wear.



Labelling

Product use
For new and previously painted walls indoors.
On concrete, lightweight concrete, plaster, gypsumboards, fibre plaster, cement fibre boards, cement chipboard.
Very suitable as a finishing coat on sand-plastered surfaces and felt.

Substrate
Must be clean, dry, solid and suitable for surface treatment.

Treatment
Remove loose material and paint by cleaning and sanding.
Previously painted surfaces are cleaned with basic cleaner.
Prime stains from water damage or tobacco with stop primer.
Cracks and holes must be filled with filler.
Chalking and porous substrates must be primed with sealer.
Apply 1-2 coats. Some colours and surfaces require an extra treatment.
Remember to ventilate after painting.

Application
Brush, roller or spray.
Decide your choice of tool/utensil depending on the finish.
Apply wet on wet and finish by brushing/rolling in the same direction.
Always use the same batch number on contiguous/unbroken surfaces.
Differences in surface structure can result in colour deviation.
Cold/heat can affect the viscosity of the material.
Material temperature for spray painting, min. 12ºC.
Condensation during drying/curing must not occur.
Cold and increased humidity extends drying time, full curing and recoat interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result
Semi-matt strong surface.
Strong especially dark shades are more delicate than light by wear and touch.
Chalking from strong shades due to excess pigment may occur.
Does not block strike-through from knots or water-soluble colourants, water stains and nicotine.
Exercise care in loading the surface until the paint is fully cured.

Cleaning and maintenance
Withstands cleaning including spot cleaning with mild detergents without abrasives, a soft brush, water and cloth.

Environmental information
Minimize your paint waste by pre-estimating how much paint you need.
Remove as much paint as possible from tools before cleaning.
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage
Cool, frost free and tightly closed

Protection equipment
Protect skin and eyes from splashes with suitable clothing, gloves and glasses.
Avoid inhalation of spray mist and grinding dust.
Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Gloss	Semi Matte;25
Density (kgs/l)	1.23
Solids Weight %	52
Solids Vol. %	41
Nominal spreading rate (m²/ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Dry to touch at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	28
Washability acc. to EN-13300/ISO-11998	Class 1
Dilution	Water, is usually not diluted
Cleaning of Tools etc.	Water
Country of Origin	Denmark

Current TDS Version

December 2025

Replaces TDS Version

February 2025