Paint Remover



Product properties
Agent for effective removal of old paint and varnish. The product is bio-based and biodegradable. Does not corrode metal or glass.

- **Ready to use**
- **Efficient**
- **Biodegradable**

Product use
Used for effective removal of old paint.
Suitable for removing acrylic, alkyd, linseed oil, plastisol and old floor paint.
Does not dissolve UV-cured/hard colours such as car lacquer.
Can be used on all types of substrates.

Substrate
Must be clean, dry and firm.

Treatment
Remove dirt, grime and grease by cleaning with a suitable cleaning agent.
Apply Paint Remover and clean the surface.
After stripping down wood substrates, clean the surface with Natural Wood Cleaner before re-treatment.
On other surfaces, wash with Fluren 37 diluted according to the instructions for use.
The surface must be completely dry before subsequent treatment.
Always carry out a test application on a small area to check and approve the result.

Application
Clean the surface and apply the product with a brush or roller.
Leave on for 30-60 minutes, the product should not dry completely.
Scrape off any loose paint.
Reapply if necessary, e.g. if there are several layers of paint to be removed.
Collect paint residue for disposal.

Expected result
Cleaned surface ready for new treatment with paint or varnish.

Environmental information
Minimize your paint waste by pre-estimating how much paint you need.
Remove as much paint as possible from tools before cleaning.
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage
Cool, frost free and tightly closed

Protection equipment
Protect skin and eyes from splashes with suitable clothing, gloves and glasses.
Avoid inhalation of spray mist and grinding dust.
Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

pH	9
Nominal spreading rate (m²/ltr.)	5
Min. working temp. during application and drying/curing	Min. +10°C
Dilution	Ready-to-use
Cleaning of Tools etc.	Water
Country of Origin	Sweden

Current TDS Version

November 2026

Replaces TDS Version

September 2025