

Wall Primer Structure

Product properties

White fine-grained structure paint that gives a fine, sandy texture. A decorative effect can be achieved – from fine to coarse structure – depending on dilution or the tools used.

- Fine-grained structure paint
- Sandy structure
- Decorative effect



Product use

Used indoors for treating and structuring walls and ceilings.
Covers minor cracks in the substrate.

Substrate

Must be primed, clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.
Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.
Water-soluble discolouration, nicotine and soot can be cleaned with Fluren 49.
Sand surface to matt finish as required.
Cracks, unevenness and holes must be filled.
Absorbent and porous substrates must be primed with Flügger Sealer.

Application

Wide brush or roller.
Decide your choice of tool/utensil depending on the finish.
The finest texture is achieved by using a brush or short-nap roller.
A coarser texture can be achieved by using a long-pile roller or a coarse-pored foam roller.
An effect texture can be achieved with a trowel, by dabbing with a brush, or with a similar tool.
Can be applied in a layer thickness of up to 2-3 mm.
Apply wet on wet.
Cold/heat can affect the viscosity of the material.
Condensation during drying/curing must not occur.
Cold and increased humidity extends drying time, full curing and recoat interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Full-matt, covered surface.
Finish treat with paint in desired gloss and colour.
Exercise care in loading the surface until the paint is fully cured.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.
Remove as much paint as possible from tools before cleaning.
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.
Avoid inhalation of spray mist and grinding dust.
Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Gloss	Full Matte
Density (kgs/l)	1.72
Solids Weight %	73
Solids Vol. %	53
Nominal spreading rate (m ² /ltr.)	2
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max. humidity 80 % RH.
Dry to touch at 20° C, 60 % RH (Hours)	1
Recoat interval at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Water, is normaly not diluted
Cleaning of Tools etc.	Water
Country of Origin	Denmark

Current TDS Version

December 2025